



LOGISTIC

STABUFILM® 65

ANTI-SLIP FILM FOR PALLET STABILIZATION



COMPOSITION

- ▶ 65 µm Medium Density polyethylene (MDPE) with high grip properties colour : transparent

PROPERTIES

- ▶ High non-slip
- ▶ Waterproof
- ▶ Transparent
- ▶ Flexible to handle curves
- ▶ Fiberless & Hygienic
- ▶ 100 % recyclable

END-USE APPLICATIONS

- ▶ Irregular shaped products
- ▶ Foil-wrap packs, plastic buckets & pails
- ▶ Cosmetic & Pharmaceutical industries
- ▶ Outdoor storage

PALLETIZATION

- ▶ Pre-cut rolls (800mm or 1000mm): width 1200mm, length 300 meters
- ▶ Rolls for automatic cutting on Excalibur: width 1200mm, diameter 1000mm

SPECIFICATION SHEET

Paper type	Medium density polyethylene film		Standards
Weight	60 g/sqm		ASTM 1894
	Non-slip on film	Non-slip on paper	
Static coefficient of friction	≥ 0,8	≥ 0,81	ASTM 1894
Dynamic coefficient of friction	≥ 0,76	≥ 0,79	ASTM 1894



TECHNICOAT
Solution

solution@cgp-coating.com - www.cgp-coating.com